

SUMMER, DIRECTIONAL

G-MAX™ RS

THE G-MAX RS IS A STYLISH, ULTRA-HIGH PERFORMANCE TIRE DESIGNED FOR MAXIMUM GRIP ON DRY AND WET ROADS GIVING YOU THE INSPIRING PERFORMANCE YOU'RE LOOKING FOR. SMART TECHNOLOGIES MAKE ANYWHERE POSSIBLE BY PROVIDING EXCEPTIONAL HANDLING RAIN OR SHINE. AND VISUAL WEAR ALERTS NOTIFY YOU OF YOUR TREAD DEPTH. THE G-MAX RS IS TRULY A SMARTER TIRE FOR A SMARTER DRIVER.

SmartGrip Technology: A strong center rib for crisp steering response. Stable shoulder blocks for maximum grip. Silica-rich summer compound and directional tread grooves ensure wet grip. Provides faster handling in dry and wet conditions and enables shorter stopping distances over leading competitors on both wet and dry roads.¹

StabiliTread™ Technology: A larger footprint and optimized pattern stiffness promote even wear and provides up to 35% longer tread life than leading competitors.²

SmartMonitor Technology: The Replacement Tire Monitor (RTM) is an indicator that is clearly visible on the tire's center rib. When the tire wears to 2/32 of tread depth the indicator transforms to read "replace tire" alerting the driver a tire change is needed.

¹ Internal handling test comparing lap times, internal wet braking test from 50 mph and dry braking test from 60 mph comparing General G-MAX RS to Firestone Firehawk Indy 500, BF Goodrich g-Force Sport Comp2 and Hankook Ventus V12 evo2 in size 245/40ZR18. On road results may vary.

² Internal tread wear testing of rear driven tires compared in size 245/40ZR18, General G-MAX RS to Firestone Firehawk Indy 500, BF Goodrich g-Force Sport Comp2 and Hankook Ventus V12 evo2. On road results may vary.



UTQG:	TREAD WEAR:	TRACTION:	TEMPERATURE:
METRIC SIZES	360	AA	A



45

DAY TRIAL
OR THE FIRST 2/32^{nds} OF TREAD

See warranty manual for complete details.

The G-MAX RS is the official tire of the new Saleen 30th Anniversary Edition Mustang.

RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER (in)	TIRE WEIGHT (LBS)	MAX. INFLATION PRESSURE (PSI)	OVERALL SECTION WIDTH (in) (MEASURING RIM)	APPROVED RIM WIDTHS (in)	MAX. LOAD (LBS)	TREAD DEPTH (in - 32mils)	REVS PER MILE	RIM PROTECT
16	55	205/55R16	91W	SL	BSW	15492560000	24.9	21.1	51	8.4 (6.5)	5.5 - 7.5	1,356	10	835	Yes
	50	225/50R16	92W	SL	BSW	15492580000	24.9	22.4	51	9.2 (7)	6 - 8	1,389	10	836	Yes
		245/50R16	97W	SL	BSW	15492600000	25.6	24.3	51	10 (7.5)	7 - 8.5	1,609	10	810	Yes
17	50	205/50R17	93W	XL	BSW	15492620000	25.1	21.0	51	8.4 (6.5)	5.5 - 7.5	1,433	10	829	Yes
		215/50R17	95W	XL	BSW	15492640000	25.5	23.0	51	8.9 (7)	6 - 7.5	1,521	10	816	Yes
		225/50R17	94W	SL	BSW	15492660000	25.9	22.9	51	9.2 (7)	6 - 8	1,477	10	803	Yes
	45	205/45R17	88W	XL	BSW	15492610000	24.3	19.4	50	8.1 (7)	6.5 - 7.5	1,235	10	856	Yes
		215/45R17	91W	XL	BSW	15492630000	24.6	22.3	51	8.4 (7)	7 - 8	1,356	10	844	Yes
		225/45R17	91W	SL	BSW	15492650000	25.0	21.1	51	8.9 (7.5)	7 - 8.5	1,356	10	832	Yes
		235/45R17	94W	SL	BSW	15492670000	25.3	22.8	51	9.3 (8)	7.5 - 9	1,477	10	820	Yes
	40	245/45R17	99Y	XL	BSW	15492700000	25.7	24.7	51	9.6 (8)	7.5 - 9	1,709	10	809	Yes
		245/40R17	91W	SL	BSW	15492690000	24.7	23.8	51	9.8 (8.5)	8 - 9.5	1,356	10	840	Yes
		255/40R17	94W	SL	BSW	15492710000	25.0	23.3	51	10.2 (9)	8.5 - 10	1,477	10	830	Yes
275/40R17	98W	SL	BSW	15492720000	25.7	25.0	51	10.9 (9.5)	9 - 11	1,653	10	810	Yes		
18	50	235/50R18	97Y	SL	BSW	15492780000	27.3	26.1	51	9.6 (7.5)	6.5 - 8.5	1,609	10	762	Yes
	45	225/45R18	91Y	SL	BSW	15492760000	26.0	22.1	51	8.9 (7.5)	7 - 8.5	1,356	10	800	Yes
		245/45R18	100Y	XL	BSW	15492820000	26.7	24.2	51	9.6 (8)	7.5 - 9	1,764	10	779	Yes
		255/45R18	103Y	XL	BSW	15492860000	27.0	27.9	51	10 (8.5)	8 - 9.5	1,929	10	768	Yes
	40	215/40R18	89Y	XL	BSW	15492730000	24.8	19.7	51	8.6 (7.5)	7 - 8.5	1,279	10	839	Yes
		225/40R18	92Y	XL	BSW	15492750000	25.1	18.8	51	9.1 (8)	7.5 - 9	1,389	10	828	Yes
		235/40R18	95Y	XL	BSW	15492770000	25.4	22.1	51	9.5 (8.5)	8 - 9.5	1,521	10	818	Yes
		245/40R18	97Y	XL	BSW	15492810000	25.7	20.2	51	9.8 (8.5)	8 - 9.5	1,609	10	808	Yes
		255/40R18	99Y	XL	BSW	15492840000	26.0	25.1	51	10.2 (9)	8.5 - 10	1,709	10	798	Yes
	275/40R18	99Y	SL	BSW	15492890000	26.7	27.0	51	10.9 (9.5)	9 - 11	1,709	10	779	Yes	
	35	245/35R18	92Y	XL	BSW	15492800000	24.8	21.7	51	9.8 (8.5)	8 - 9.5	1,389	10	839	Yes
		255/35R18	94Y	XL	BSW	15492830000	25.0	22.8	51	10.2 (9)	8.5 - 10	1,477	10	830	Yes
		265/35R18	97Y	XL	BSW	15492870000	25.3	21.4	51	10.7 (9.5)	9 - 10.5	1,609	10	821	Yes
		275/35R18	95Y	SL	BSW	15492880000	25.6	24.8	51	10.9 (9.5)	9 - 11	1,521	10	812	Yes
285/35R18	101Y	XL	BSW	15492920000	25.9	28.1	51	11.4 (10)	9.5 - 11	1,819	10	803	Yes		
30	295/30R18	98Y	XL	BSW	15492930000	25.0	25.2	51	11.9 (10.5)	10 - 11	1,653	10	832	Yes	

BSW = Black Sidewall

Continued next page

RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER (in)	TIRE WEIGHT (LBS)	MAX. INFLATION PRESSURE (PSI)	OVERALL SECTION WIDTH (in) (MEASURING RIM)	APPROVED RIM WIDTHS (in)	MAX. LOAD (LBS)	TREAD DEPTH (in - 32ms)	REVS PER MILE	RIM PROTECT
19	45	225/45R19	92Y	SL	BSW	15492950000	27.0	23.6	51	8.9 (7.5)	7 - 8.5	1,389	10	770	Yes
		245/45R19	102Y	XL	BSW	15494240000	27.7	26.2	51	9.6 (8)	7.5 - 9	1,874	10	750	Yes
	40	225/40R19	93Y	XL	BSW	15492940000	26.1	18.0	51	9.1 (8)	7.5 - 9	1,433	10	796	Yes
		245/40R19	98Y	XL	BSW	15493010000	26.7	24.6	51	9.8 (8.5)	8 - 9.5	1,653	10	778	Yes
		255/40R19	100Y	XL	BSW	15494300000	27.0	25.8	51	10.2 (9)	8.5 - 10	1,764	10	769	Yes
	35	235/35R19	91Y	XL	BSW	15492980000	25.5	22.1	51	9.5 (8.5)	8 - 9.5	1,356	10	815	Yes
		245/35R19	93Y	XL	BSW	15492990000	25.8	22.7	51	9.8 (8.5)	8 - 9.5	1,433	10	807	Yes
		255/35R19	96Y	XL	BSW	15494270000	26.0	24.4	51	10.2 (9)	8.5 - 10	1,565	10	798	Yes
		265/35R19	98Y	XL	BSW	15494360000	26.3	25.2	51	10.7 (9.5)	9 - 10.5	1,653	10	790	Yes
		275/35R19	100Y	XL	BSW	15494440000	26.6	27.8	51	10.9 (9.5)	9 - 11	1,764	10	782	Yes
	30	285/35R19	99Y	SL	BSW	15494480000	26.9	26.2	51	11.4 (10)	9.5 - 11	1,709	10	774	Yes
		275/30R19	96Y	XL	BSW	15494400000	25.5	25.8	51	10.9 (9.5)	9 - 10	1,565	10	815	Yes
		295/30R19	100Y	XL	BSW	15494490000	26.0	27.2	51	11.9 (10.5)	10 - 11	1,764	10	800	Yes
		305/30R19	102Y	XL	BSW	15494500000	26.2	26.0	51	12.3 (11)	10.5 - 11.5	1,874	10	793	Yes
	20	45	245/45R20	103Y	XL	BSW	15494540000	28.7	26.8	51	9.6 (8)	7.5 - 9	1,929	10	724
40		245/40R20	99Y	XL	BSW	15494510000	27.7	27.8	51	9.8 (8.5)	8 - 9.5	1,709	10	750	Yes
		275/40R20	106Y	XL	BSW	15494590000	28.7	30.3	51	10.9 (9.5)	9 - 11	2,094	10	725	Yes
35		275/35R20	102Y	XL	BSW	15494570000	27.6	24.4	51	10.9 (9.5)	9 - 11	1,874	10	753	Yes
		285/35R20	100Y	SL	BSW	15501340000	27.9	29.5	51	11.4 (10)	9.5 - 11	1,764	10	746	Yes
	305/35R20	104Y	SL	BSW	15501350000	28.4	32.5	51	12.3 (11)	10 - 12	1,984	10	731	Yes	

BSW = Black Sidewall