

GRANDTREK® AT23

Original Equipment All-Season Truck and SUV Tire



GRANDTREK AT23 TREAD PATTERN



FEATURES

M+S-rated all-season tread pattern

Circumferential tread grooves

Advanced tread

5-Pitch Technology™

BENEFITS

Aids control in all-season conditions

Help evacuate water away from the footprint for excellent wet traction

Enhanced wet-weather performance

Aids noise reduction for a quiet ride

GRANDTREK AT23 SPECIFICATIONS

SIZE	SERVICE DESCRIPTION	LOAD RANGE	SIDEWALL	PRODUCT CODE	MATERIAL NUMBER	APPROVED RIM WIDTH (INS)	MEASURING RIM WIDTH (INS)	SECTION WIDTH (INS)	OVERALL DIAMETER (INS)	MAX LOAD (LBS)	TREAD DEPTH (IN 32NDS)	REVS/ MILE	UTQG	ORIGINAL EQUIPMENT FITMENT
265/70R18	116H	SL	BSW	290014826	232659	7.0 - 9.0	8	10.7	32.6	2,756	11	641	360 A A	NISSAN ARMADA (17-21)
P275/60R18	111H	SL	BSW	290014824	185301	7.5 - 9.5	8	11	31	2,403	12	675	360 A A	
285/60R18	116V	SL	SBL	290014825	231001	8.0 - 10.0	8.5	11.5	31.5	2,756	11	664	360 A A	LEXUS LX (15-21)
P285/60R18	114V	SL	BSW	290014840	205267	8.0 - 10.0	8.5	11.5	31.5	2,601	11	663	360 A A	TOYOTA LAND CRUISER (13-15)
265/55R19	109V	SL	BLT	290014827	240077	7.5 - 9.5	8.5	10.91	30.5	2,271	9	685	360 B A	LEXUS GX (20-21)

Do not attempt to mount 16" rim diameter tires on 16.5" rim diameter wheels; this may result in serious injury or death. Always maintain tire inflation pressure at levels recommended by the vehicle manufacturer as shown on the vehicle placard or in the owner's manual.

For more complete information, go to Tire-HQ™ at www.tire-hq.com.

NOTE: When replacing a vehicle's original equipment light truck tires with passenger car tires, the load on each replacement car tire must not exceed the maximum load stamped on the replacement car tire sidewall divided by 1.10.



On-Road



Chosen as Original Equipment by Global Vehicle Manufacturers